

<h1 style="margin: 0;">SPECIAL PACKAGING INSTRUCTION</h1>				Form Approved OMB No. 0704-0188		<b>XRJ</b>
Public reporting burden for this collection of information is estimated to average 30 days per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, Va 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project(0704-0188), Washington, DC 20503. Please do not return your form to either of these addresses.						
<b>1. PART OR DRAWING NO. (CAGE) NOMENCLATURE</b> 57K3398 (19207) KIT, BUMPER			<b>2. CAGE</b> 19207		<b>3. SPI NO.</b> AK14895929	
<b>4. NATIONAL STOCK NO.</b> 2540-01-489-5929			<b>5. DATE OF DRAWING</b> May 14, 2002		<b>6. REVISION</b>	
<b>7. QUP</b> 1 EA	<b>8. ICQ</b> NONE	<b>9. UNIT PACK WT. (LB)</b> 36.0	<b>10. UNIT PACK CU (CU. FT.)</b> 0.724		<b>11. UNIT PACK SIZE (INCHES)</b>	
		<b>18. STEPS</b>	<b>19. REQD</b>	<b>20. DESCRIPTION</b>		
12. MILITARY PRESERVATION MIL-STD-2073-1D, METHOD: See Block				SEE BLOCK 17		
13. CLEANING MIL-STD-2073-1D, CODE 1						
14. DRYING MIL-STD-2073-1D						
15. PACKING						
a. LEVEL A MIL-STD-2073-1D AND NOTE B						
b. LEVEL B MIL-STD-2073-1D AND NOTE B						
16. MARKING MIL-STD-129						
<b>17. NOTES/DRAWING</b>  QUALITY ASSURANCE PROVISIONS: INSPECT THE PRESERVATION AND UNIT PACK IN ACCORDANCE WITH MIL-STD-1D. INSPECT PACKING WITH MIL-STD-2073-1D AND APPLICABLE CONTAINER SPEVIFICATION(S).  PRESERVE AND PACK IAW MIL-STD-2073-1D, APPENDIX D;  A. KIT CONTENTS LIST:  THIS KIT, CONSISTS OF THE ITEMS SHOWN ON DRAWING P/N 57K3398 (19207).  B. LEVEL A: USING A CLEATED PLYWOOD BOX, CONFORMING TO ASTM-D6251, TYPE III, CLASS 2. (NOT TO EXCEED 1000 POUNDS).  LEVEL B: USING CONTAINER: ASTM-D5118, TYPE CF, CLASS WR, SEALED AND REINFORCED IN ACCORDANCE WITH ASTM-D1974, METHOD 2C OR 2D.  FOR BOTH LEVEL A AND LEVEL B, WHEN THE TOTAL QUANTITY TO BE SHIPPED TO THE SAME DESTINATION EXCEEDS 125 POUNDS, EXTERIOR PACKS WITHOUT SKIDS SHALL BE PALLETIZED. MIL-HDBK-774 MAY BE USED FOR GUIDANCE. WHERE POSSIBLE USE A STANDARD 40 X 48 PALLET WITH A MAXIMUM OF 2 INCH OVERHANG. MAXIMUM HEIGHT OF PALLET LOAD IS 54 INCHES. MAXIMUM LOAD GROSS WEIGHT IS 4000 LBS.  <b>THE ABOVE ARE ESTIMATED PACKAGING DATA. THE CONTRACTOR SHALL DETERMINE PROPER PACKAGING MATERIALS AND SIZES.</b>						